






























GOLD STAR

PDA No :NP/18215 dt19.12.18

Application Area			Residential Usage
Characteristics	Test Method	Symbol	Results
Thickness (mm)	EN 428 ISO 24346		0.60
Roll width (mm)	EN 426 ISO 24341		2000
Roll length (mm)	EN 426 ISO 24341		40000
Tile size (mm)	EN 427		N/A
Total weight (kgs/sq-mtr)	EN 430 ISO 23997		1.10
Surface Protection	PUR		N/A
Slip resistance	DIN 51130 ASTM D2047		N/A
Residual Indentation (mm)	EN 433 ISO 23343-1 ASTM F970		N/A
Flexibility (mm)	EN 435 ISO 24344 ASTM F137		40 mm mandrel, passed
Dimensional stability (%)	EN 434 ISO 23999		N/A
Bearing a castor chair	EN 425 ISO 4918		N/A
Performance classification	EN 685 ISO 10874		21,22
Electrical Resistance(Ω)	EN 1081		N/A
Static Electrical Propensity (KV)	EN 1815		N/A
Thermal Resistance (m2k/w)	EN 12664 ISO 8302 ASTM 1514		N/A
Hygiene / Clean room test	ISO 14644-1		N/A
Anti-fungal/Anti-bacterial Class Room	ISO846 A,C ISO 22196		N/A
Formaldehyde Emission (HCHO)	EN 717-1:2004		N/A
Abrasion Resistance Volume loss (weight loss/1000 cycle)	EN 660-2 EN 649 ASTMD 3389(8)		N/A
Sound Absorption	ISO 140-8 EN ISO 717-2		N/A
Stain Resistance	EN 423 ISO 26987		N/A
Resistance to chemicals	ASTM F925		No Visible Change
Colour fastness (Deg) (ΔE)	ISO 105-BO2 ASTM F1515		N/A
Smoke Density (Δm)	ASTM E662-05		N/A
Surface Spread of flame	BS 476 PART 7		N/A
Fire Propagation	BS 476 PART 6		N/A
Reaction to Fire (kw/m2) - Class Type	EN ISO 9239-1 EN ISO 11925-2 EN135011:2007+A ASTME-648-06	 	N/A
Maritime Usages			N/A