

Tests

EN/GOST

GENERAL DATA ON PRODUCT COMPOSITION		
Type of covering:	Flooring panel with top layer made from specially-resined decor paper	
Effective measurement:	1380 193 x 8mm	
Product structure:	1. Protective layer	
	2. Decorative paper	
	3. HDF board	
	4. Stabilizing layer	
TECHNICAL DATA		
Lock system:		UNICLIC
Wear class:	EN 13329	32
Wear resistance	EN 13329	AC4
Floor area per pack		2,131 m <sup>2</sup>
Number of board per pack		8pcs.
Pack weight		14,56kg
Number of packs on pallet		60
Chamfer		no
Surface structure		T (rustic)

Item	Mark	Meaning/Decoding definition
1.		Hygienic, does not require any special treatment, easily cleaned sweeping or wiping with a rag is sufficient
2.		Impact resistant. Highly resistant to various mechanical damages
3.		Resistant to high temperatures (for instance, to smoldering cigarettes)
4.		Resistant to sunlight. Neither color, nor glossiness change if exposed to sunlight
5.		Resistant to stains and chemical exposure
6.		Resistant to wear-out when moving furniture
7.		Good heat conductivity. Can be used for heated floors
8.		The base is of the wood -based high-density fiberboard (HDF)
9.		Quick and easy assembly and disassembly
10.		Environment-friendly
11.		Resistant to scratching
12.		Emission class 1 guaranteeing a low formaldehyde contents in the material of the board
13.		Antistatic (does not attract dust)
14.		Fire resistance class

